



Соединительная муфта GRIP Ø25.0-48.3, EPDM, W5 d26

Артикул	Диаметр OD (мм)	Допуск на диаметр (мм)	PN (бар)	B (мм)	C (мм)	DV (мм)	X (мм)	Зазор без вкладки R (мм)	Зазор со вкладкой R (мм)	Крутящий момент Nm	sw(мм)	Резьба метрическая
G19122	21.3	21.0-21.6	36	46.5/75	18	43	56	5	5-10	10	6	6
G20041	25	24.5-25.5	64	46.5/75	18	41	53	5	5-10	10	6	8
G20000	26.9	26.4-27.4	58	46.5/75	18	44	56	5	5-10	10	6	8
G20025	28	27.5-28.5	50	46.5/75	18	45	57	5	5-10	10	6	8
G20050	30	21.0-21.6	42	46.5/75	18	47	60	5	5-10	10	6	8
G20100	33.7	33.2-34.2	39	46.5/75	18	51	65	5	5-10	10	6	8
G20124	35	34.5-35.5	37	46.5/75	18	52	66	5	5-10	12	6	8
G20150	38	37.5-38.5	36	46.5/75	18	55	69	5	5-10	12	6	8
G20175	40	39.5-40.5	35	46.5/75	18	57	71	5	5-10	12	6	8
G20200	42.4	41.9-42.9	33	46.5/75	18	60	74	5	5-10	12	6	8
G20250	44.5	44.0-45.0	30	46.5/75	18	62	76	5	5-10	12	6	8
G20300	48.3	47.8-48.8	28	46.5/75	18	65	81	5	5-10	12	6	8