



Соединительная муфта GRIP Ø54.0-168.3, EPDM, W5 d127

Артикул	Диаметр OD (мм)	Допуск на диаметр (мм)	PN (бар)	B (мм)	C (мм)	DV (мм)	X (мм)	Зазор без вкладки R (мм)	Зазор со вкладкой R (мм)	Крутящий момент Nm	sw(мм)	Резьба метрическая
G20700	100.6	99.6-101.6	10	100	40	124	146	5-10	5-10	25	6	10
G21300	159	157.4-160.6	16	115	53	186	208	5-10	5-30	50	6	12
G21350	168.3	166.6-170.0	16	115	53	195	217	5-10	5-30	50	6	12
G20350	54	53.5-54.5	24	65	24	71	87	5	5-15	15	6	8
G20400	57	56.4-57.6	23	65	24	74	90	5	5-15	15	6	8
G20470	66.6	64.9-67.3	22	65	24	84	100	5	5-15	15	6	8
G20485	70	68.9-70.1	22	65	24	87	104	5	5-15	15	6	8
G20667	95	94.0-96.0	24	100	40	117	139	5-10	5-25	25	6	10
G20850												
G20900	114.3	113.2-115.4	24	100	40	138	160	5-10	5-25	25	6	10
G21100	133	131.7-134.3	23	115	53	160	182	5-10	5-30	40	6	12
G20930	118	116.9-119.1	22	100	40	142	166	5-10	5-25	35	6	10
G20750	101.6	100.6-102.6	26	100	40	125	146	5-10	5-25	25	6	10
G20450	60.3	59.7-60.9	23	65	24	77	93	5	5-15	15	6	8
G20950	127	125.7-128.3	23	115	53	154	176	5-10	5-30	40	6	12
G21150	139.7	138.3-141.0	20	115	53	166	189	5-10	5-30	40	6	12
G20650	88.9	88.0-89.8	26	100	40	112	134	5-10	5-25	20	6	10
G20940												
G21328	165	163.4-166.6	16	115	53	192	214	5-10	5-30	50	6	12
G20500	73	72.3-73.7	21	65	24	90	107	5	5-15	15	6	8
G20600	84	83.2-84.8	29	100	40	107	130	5-10	5-25	20	6	10
G20800	104	103.0-105.0	28	100	40	127	148	5-10	5-25	25	6	10
G21200	141.3	139.9-142.7	20	115	53	168	190	5-10	5-30	40	6	12
G21225	144	142.6-145.4	20	115	53	171	183	5-10	5-30	60	6	12
G21250	154	152.5-155.5	18	115	53	181	203	5-10	5-30	50	6	12

G20550	76.1	75.3-76.9	35	100	40	100	122	5-10	5-25	20	6	10
G20570	79.5	78.7-80.3	32	100	40	103	125	5-10	5-25	20	6	10
G20690	98	97-99.0	24	100	40	121	143	5	5-25	35	6	10
G20825	104.8	103.8-105.8	28	100	40	128	150	5-10	5-25	25	6	10
G21000	129	127.7-130.3	23	115	53	156	178	5-10	5-30	40	6	12
G21050	130.2	128.9-131.5	25	115	53	157	179	5-10	5-30	40	6	12
G20425	63	62.4-63.6	23	65	24	80	96	5	5-15	15	6	8