



Тройник редукционный для стыковой сварки PP-H FIP 250x110 SDR11 PN6

Артикул	d1	d2	i1	l2	L	s1	s2	Z2	g
TRBM17063050	*63	50	63	56	220	3.8	3	103	210
TRBM17075050	*75	50	70	55	253	4.5	3	113	410
TRBM17075063	*75	63	70	63	260	4.5	3.8	117	420
TRBM17090063	*90	63	79	63	275	5.4	3.8	137	570
TRBM17090075	*90	75	74	70	278	5.4	4.5	138	570
TRBM17110063	*110	63	85	66	315	6.6	3.8	159	960
TRBM17110075	*110	75	82	70	315	6.6	4.5	157	850
TRBM17110090	*110	90	82	79	315	6.6	5.4	155	900
TRBM17125063	*125	63	70	31	271	7.4	3.8	112	1030
TRBM17125110	*125	110	87	82	340	7.4	6.6	170	1240
TRBM17140063	140	63	83	32	291	8.0	3.6	120	1290
TRBM17140075	140	75	81	35	291	8.0	4.3	120	1370
TRBM17140090	140	90	81	41	291	8.0	5.1	130	1380
TRBM17140110	140	110	50	44	291	8.0	6.3	140	1600
TRBM17160063	*160	63	98	64	347	9.5	3.8	175	1850
TRBM17160075	*160	75	98	75	348	9.5	4.5	179	1910
TRBM17160090	*160	90	100	81	349	9.5	5.4	182	1940
TRBM17160110	*160	110	98	85	400	9.5	6.6	202	2360
TRBM17160125	160	125	58	47	315	9.1	7.1	150	2060
TRBM17180075	180	75	112	30	348	10.2	4.3	160	2230
TRBM17180063	180	63	125	30	348	10.2	3.6	140	2160
TRBM17225160	*225	160	120	98	498	13.4	9.5	250	6130
TRBM17225180	*225	180	134	134	558	13.4	10.7	280	7100
TRBM11063050	*63	50	63	56	215	5.8	4.6	103	300
TRBM11075032	*75	32	70	46	256	6.8	2.9	103	500
TRBM11075050	*75	50	70	56	253	6.8	4.6	113	540
TRBM11075063	*75	63	70	63	255	6.8	5.8	117	560
TRBM11090032	90	32	53	23	203	8.2	2.9	85	560
TRBM11090050	90	50	53	28	213	8.2	4.6	100	580

TRBM11090063	*90	63	82	66	282	8.2	5.8	127	790
TRBM11090075	*90	75	73	68	280	8.2	6.8	138	800
TRBM11110032	110	32	66	22	234	10.0	2.9	91	940
TRBM11110050	110	50	66	27	240	10.0	4.6	101	950
TRBM11110063	*110	63	88	68	328	10.0	5.8	149	1345
TRBM11110075	*110	75	86	70	320	10.0	6.8	151	1250
TRBM11110090	*110	90	86	79	320	10.0	8.2	158	1440
TRBM11125063	125	63	54	25	254	10.0	5.8	107	1360
TRBM11125090	*125	90	-	-	340	11.4	8.2	170	1660
TRBM11125110	*125	110	90	83	341	11.4	10	170	1860
TRBM11140063	140	63	83	32	291	12.7	5.8	120	1740
TRBM11140075	140	75	81	35	291	12.7	6.8	130	1840
TRBM11140090	140	90	81	41	291	12.7	8.2	130	1960
TRBM11140110	140	110	50	44	291	12.7	10	140	2200
TRBM11160063	*160	63	100	67	347	14,6	5,8	175	2640
TRBM11160075	*160	75	98	74	343	14.6	6.8	180	2560
TRBM11160090	*160	90	104	83	412	14.6	8.2	190	3685
TRBM11160110	*160	110	104	89	414	14.6	10	200	3685
TRBM11160125	160	125	58	47	315	14.6	11.4	150	2750
TRBM11180063	180	63	125	30	348	16.4	5.8	140	2980
TRBM11180075	180	75	112	30	348	16.4	6.8	160	3060
TRBM11180090	*180	90	-	-	427	16.4	8.2	200	4360
TRBM11180110	*180	110	-	-	464	16.4	10	225	4640
TRBM11180125	180	125	-	-	366	16.4	11.4	166	3220
TRBM11200090	*200	90	122	79	498	18.2	5.1	207	6550
TRBM11200063	*200	63	122	63	500	18.2	5.8	190	5700
TRBM11200110	*200	110	122	82	500	18.2	6.3	215	7040
TRBM11225075	*225	75	120	70	555	20.5	6.8	227	6400
TRBM11225090	*225	90	129	82	556	20.5	8.2	228	9380
TRBM11225110	*225	110	130	86	556	20.5	10	238	6600
TRBM11200125	*200	125	115	43	388	18.2	11.4	165	6920
TRBM11200160	*200	160	122	98	500	18.2	9.1	234	8300
TRBM11225125	225	125	135	40	456	20.5	11.4	178	6120
TRBM11250110	*225	180	135	135	558	20.5	16,4	280	9540
TRBM11250160	*250	110	135	38	450	22.7	10	197	7700
TRBM11315110	*250	160	110	58	458	22.7	14.6	213	8040
TRBM11315225	*315	160	150	102	695	28.6	14.6	290	16600
TRBM11225180	225	160	101	98	498	20.5	14,6	247	8280

TRBM11315160	*315	110	150	82	695	28.6	10	277	15280
TRBM11315250	*315	225	-	-	650	28.6	20.5	335	24820