




Отвод 45° для стыковой сварки PP-H FIP d20 SDR11 PN6

| Артикул  | d   | L   | s   | Z    | g     |
|----------|-----|-----|-----|------|-------|
| HBM17050 | 50  | 62  | 76  | 2,9  | 80    |
| HBM17063 | 63  | 66  | 88  | 3,6  | 142   |
| HBM17140 | 140 | 120 | 168 | 8    | 1245  |
| HBM17160 | 160 | 143 | 190 | 9,1  | 1850  |
| HBM17180 | 180 | 141 | 196 | 10,2 | 2335  |
| HBM17225 | 225 | 153 | 210 | 12,8 | 3970  |
| HBM17250 | 250 | 133 | 220 | 14,2 | 5780  |
| HBM11020 | 20  | 52  | 72  | 1,9  | 19    |
| HBM11025 | 25  | 57  | 76  | 2,3  | 30    |
| HBM11032 | 32  | 71  | 90  | 2,9  | 56    |
| HBM11040 | 40  | 73  | 95  | 3,7  | 88    |
| HBM11050 | 50  | 62  | 76  | 4,6  | 110   |
| HBM11063 | 63  | 66  | 88  | 5,8  | 205   |
| HBM11075 | 75  | 71  | 90  | 6,8  | 290   |
| HBM11090 | 90  | 83  | 105 | 8,2  | 460   |
| HBM11110 | 110 | 93  | 121 | 10   | 785   |
| HBM11125 | 125 | 98  | 137 | 11,4 | 1130  |
| HBM11140 | 140 | 122 | 168 | 12,7 | 1685  |
| HBM11160 | 160 | 143 | 190 | 14,6 | 2550  |
| HBM11180 | 180 | 141 | 196 | 16,4 | 3285  |
| HBM11200 | 200 | 153 | 207 | 18,2 | 4540  |
| HBM11225 | 225 | 153 | 210 | 20,5 | 5750  |
| HBM11280 | 280 | 143 | 227 | 25,4 | 10060 |

|          |     |     |     |      |       |
|----------|-----|-----|-----|------|-------|
| HBM11315 | 315 | 155 | 250 | 28,6 | 13675 |
| HBM17075 | 75  | 71  | 90  | 4,3  | 196   |
| HBM17090 | 90  | 82  | 105 | 5,1  | 325   |
| HBM17110 | 110 | 93  | 121 | 6,3  | 560   |
| HBM17125 | 125 | 98  | 137 | 7,1  | 790   |
| HBM17200 | 200 | 152 | 207 | 11,4 | 3130  |
| HBM17280 | 280 | 142 | 227 | 15,9 | 7285  |
| HBM17315 | 315 | 155 | 250 | 17,9 | 9850  |
| HBM11250 | 250 | 134 | 220 | 22,7 | 7875  |