



Соединительная муфта GRIP Ø25.0-48.3, NBR, W5 d38

| Артикул | Диаметр<br>OD<br>(мм) | Допуск<br>на<br>диаметр<br>(мм) | PN<br>(бар) | B (мм)  | C (мм) | DV<br>(мм) | X (мм) | Зазор<br>без<br>вкладки<br>R (мм) | Зазор<br>со<br>вкладкой<br>R (мм) | Крутящий<br>момент<br>Nm | sw(мм) | Резьба<br>метрическая |
|---------|-----------------------|---------------------------------|-------------|---------|--------|------------|--------|-----------------------------------|-----------------------------------|--------------------------|--------|-----------------------|
| G19126  | 21.3                  | 21.0-21.6                       | 36          | 46.5/75 | 18     | 43         | 56     | 5                                 | 5-10                              | 10                       | 6      | 6                     |
| G20040  | 25                    | 24.5-25.5                       | 64          | 46.5/75 | 18     | 41         | 53     | 5                                 | 5-10                              | 10                       | 6      | 8                     |
| G20001  | 26.9                  | 26.4-27.4                       | 58          | 46.5/75 | 18     | 44         | 56     | 5                                 | 5-10                              | 10                       | 6      | 8                     |
| G20026  | 28                    | 27.5-28.5                       | 50          | 46.5/75 | 18     | 45         | 57     | 5                                 | 5-10                              | 10                       | 6      | 8                     |
| G20051  | 30                    | 21.0-21.6                       | 42          | 46.5/75 | 18     | 47         | 60     | 5                                 | 5-10                              | 10                       | 6      | 8                     |
| G20101  | 33.7                  | 33.2-34.2                       | 39          | 46.5/75 | 18     | 51         | 65     | 5                                 | 5-10                              | 10                       | 6      | 8                     |
| G20125  | 35                    | 34.5-35.5                       | 37          | 46.5/75 | 18     | 52         | 66     | 5                                 | 5-10                              | 12                       | 6      | 8                     |
| G20151  | 38                    | 37.5-38.5                       | 36          | 46.5/75 | 18     | 55         | 69     | 5                                 | 5-10                              | 12                       | 6      | 8                     |
| G20176  | 40                    | 39.5-40.5                       | 35          | 46.5/75 | 18     | 57         | 71     | 5                                 | 5-10                              | 12                       | 6      | 8                     |
| G20201  | 42.4                  | 41.9-42.9                       | 33          | 46.5/75 | 18     | 60         | 74     | 5                                 | 5-10                              | 12                       | 6      | 8                     |
| G20251  |                       |                                 |             |         |        |            |        |                                   |                                   |                          |        |                       |
| G20301  | 48.3                  | 47.8-48.8                       | 28          | 46.5/75 | 18     | 65         | 81     | 5                                 | 5-10                              | 12                       | 6      | 8                     |