



Соединительная муфта GRIP Ø54.0-168.3, EPDM, W5 d125

| Артикул | Диаметр OD (мм) | Допуск на диаметр (мм) | PN (бар) | B (мм) | C (мм) | DV (мм) | X (мм) | Зазор без вкладки R (мм) | Зазор со вкладкой R (мм) | Крутящий момент Nm | sw(мм) | Резьба метрическая |
|---------|-----------------|------------------------|----------|--------|--------|---------|--------|--------------------------|--------------------------|--------------------|--------|--------------------|
| G20700 | 100.6 | 99.6-101.6 | 103 | 100 | 40 | 124 | 146 | 5-10 | 5-10 | 25 | 6 | 10 |
| G20750 | 101.6 | 100.6-102.6 | 103 | 100 | 40 | 125 | 146 | 5-10 | 5-25 | 25 | 6 | 10 |
| G20800 | 104 | 103.0-105.0 | 103 | 100 | 40 | 127 | 148 | 5-10 | 5-25 | 25 | 6 | 10 |
| G20825 | 104.8 | 103.8-105.8 | 103 | 100 | 40 | 128 | 150 | 5-10 | 5-25 | 25 | 6 | 10 |
| G20850 | | | | | | | | | | | | |
| G20900 | 114.3 | 113.2-115.2 | 102 | 100 | 40 | 138 | 160 | 5-10 | 5-25 | 25 | 6 | 10 |
| G20930 | 118 | 116.9-119.2 | 102 | 100 | 40 | 142 | 166 | 5-10 | 5-25 | 35 | 6 | 10 |
| G20940 | | | | | | | | | | | | |
| G20950 | 127 | 125.7-128.3 | 103 | 115 | 53 | 154 | 176 | 5-10 | 5-30 | 40 | 6 | 12 |
| G21000 | 129 | 127.7-130.3 | 103 | 115 | 53 | 156 | 178 | 5-10 | 5-30 | 40 | 6 | 12 |
| G21050 | 130.2 | 128.9-131.5 | 103 | 115 | 53 | 157 | 179 | 5-10 | 5-30 | 40 | 6 | 12 |
| G21100 | 133 | 131.7-134.3 | 103 | 115 | 53 | 160 | 182 | 5-10 | 5-30 | 40 | 6 | 12 |
| G21150 | 139.7 | 138.3-141.0 | 103 | 115 | 53 | 166 | 189 | 5-10 | 5-30 | 40 | 6 | 12 |
| G21200 | 141.3 | 139.9-142.0 | 103 | 115 | 53 | 168 | 190 | 5-10 | 5-30 | 40 | 6 | 12 |
| G21225 | 144 | 142.6-145.0 | 103 | 115 | 53 | 171 | 183 | 5-10 | 5-30 | 60 | 6 | 12 |
| G21250 | 154 | 152.5-155.8 | 103 | 115 | 53 | 181 | 203 | 5-10 | 5-30 | 50 | 6 | 12 |
| G21300 | 159 | 157.4-160.6 | 103 | 115 | 53 | 186 | 208 | 5-10 | 5-30 | 50 | 6 | 12 |
| G21328 | 165 | 163.4-166.6 | 103 | 115 | 53 | 192 | 214 | 5-10 | 5-30 | 50 | 6 | 12 |
| G21350 | 168.3 | 166.6-170.6 | 103 | 115 | 53 | 195 | 217 | 5-10 | 5-30 | 50 | 6 | 12 |
| G20350 | 54 | 53.5-54.5 | 124 | 65 | 24 | 71 | 87 | 5 | 5-15 | 15 | 6 | 8 |
| G20400 | 57 | 56.4-57.6 | 123 | 65 | 24 | 74 | 90 | 5 | 5-15 | 15 | 6 | 8 |
| G20450 | 60.3 | 59.7-60.9 | 123 | 65 | 24 | 77 | 93 | 5 | 5-15 | 15 | 6 | 8 |
| G20425 | 63 | 62.4-63.6 | 123 | 65 | 24 | 80 | 96 | 5 | 5-15 | 15 | 6 | 8 |
| G20470 | 66.6 | 64.9-67.3 | 122 | 65 | 24 | 84 | 100 | 5 | 5-15 | 15 | 6 | 8 |
| G20485 | 70 | 68.9-70.7 | 122 | 65 | 24 | 87 | 104 | 5 | 5-15 | 15 | 6 | 8 |
| G20500 | 73 | 72.3-73.7 | 121 | 65 | 24 | 90 | 107 | 5 | 5-15 | 15 | 6 | 8 |
| G20550 | 76.1 | 75.3-76.9 | 135 | 100 | 40 | 100 | 122 | 5-10 | 5-25 | 20 | 6 | 10 |
| G20570 | 79.5 | 78.7-80.3 | 132 | 100 | 40 | 103 | 125 | 5-10 | 5-25 | 20 | 6 | 10 |
| G20600 | 84 | 83.2-84.8 | 129 | 100 | 40 | 107 | 130 | 5-10 | 5-25 | 20 | 6 | 10 |
| G20650 | 88.9 | 88.0-89.8 | 126 | 100 | 40 | 112 | 134 | 5-10 | 5-25 | 20 | 6 | 10 |

| | | | | | | | | | | | | |
|--------|----|-----------|----|-----|----|-----|-----|------|------|----|---|----|
| G20667 | 95 | 94.0-96.0 | 24 | 100 | 40 | 117 | 139 | 5-10 | 5-25 | 25 | 6 | 10 |
| G20690 | 98 | 97-99.0 | 24 | 100 | 40 | 121 | 143 | 5 | 5-25 | 35 | 6 | 10 |