



Соединительная муфта GRIP Ø25.0-48.3, NBR, W5 d21

Артикул	Диаметр OD (мм)	Допуск на диаметр (мм)	PN (бар)	B (мм)	C (мм)	DV (мм)	X (мм)	Зазор без вкладки R (мм)	Зазор со вкладкой R (мм)	Крутящий момент Nm	sw(мм)	Резьба метрическая
G20101	33.7	33.2-34.2	339	46.5/75	18	51	65	5	5-10	10	6	8
G20001	26.9	26.4-27.4	458	46.5/75	18	44	56	5	5-10	10	6	8
G20026	28	27.5-28.5	550	46.5/75	18	45	57	5	5-10	10	6	8
G20151	38	37.5-38.5	536	46.5/75	18	55	69	5	5-10	12	6	8
G20176	40	39.5-40.5	535	46.5/75	18	57	71	5	5-10	12	6	8
G20301	48.3	47.8-48.8	828	46.5/75	18	65	81	5	5-10	12	6	8
G20251												
G19126	21.3	21.0-21.6	536	46.5/75	18	43	56	5	5-10	10	6	6
G20040	25	24.5-25.5	564	46.5/75	18	41	53	5	5-10	10	6	8
G20051	30	21.0-21.6	542	46.5/75	18	47	60	5	5-10	10	6	8
G20125	35	34.5-35.5	537	46.5/75	18	52	66	5	5-10	12	6	8
G20201	42.4	41.9-42.9	933	46.5/75	18	60	74	5	5-10	12	6	8