



Муфта соединительная Straub-METAL-GRIP Ø180.0-609.6, NBR, W1 d355

Артикул	Диаметр OD (мм)	Допуск на диаметр (мм)	PN (бар)	B (мм)	C (мм)	DV (мм)	X (мм)	Зазор без вкладки R (мм)	Зазор со вкладкой R (мм)	Крутящий момент Nm	sw (мм)	Резьба метрическая
1573	244.5	242.0 - 247.0	27	148	67	290	330	5-15	5-25	180	17	20
1614	558.8	554.0 - 564.0	6	148	67	604	649	5-15	5-25	300	17	20
1651	180	178.0 - 182.0	29	148	67	225	256	5-15	5-25	150	17	20
1542	193.7	192.0 - 195.5	29	148	67	239	270	5-15	5-25	150	17	20
1654	206	204.0 - 208.0	28	148	67	251	282	5-15	5-25	180	17	20
1575	267	264.5 - 269.5	24	148	67	312	352	5-15	5-25	180	17	20
1568	273	270.5 - 275.5	21	148	67	318	359	5-15	5-25	180	17	20
1577	323.9	320.5 - 327.0	18	148	67	369	411	5-15	5-25	230	17	20
1610	457.2	452.5 - 462.0	8	148	67	502	546	5-15	5-25	250	17	20
1616	609.6	604.5 - 614.5	5	148	67	655	701	5-15	5-25	300	17	20
1653	200	198.0 - 202.0	28	148	67	245	276	5-15	5-25	180	17	20
1578												
1608	406.4	402.5 - 410.5	14	148	67	451	494	5-15	5-25	230	17	20
1612	508	503.0 - 513.0	6	148	67	553	598	5-15	5-25	250	17	20