



Напорная труба ХПВХ (IPS) d400

Артикул	d	PN	Толщина стенки, мм	Длина, м	Вес, кг/м
PIPEC13016	16	16	1,4	5	0,110
IPIPEC16020	20	16	2,3	4	—
IPIPEC16025	25	16	2,8	4	—
IPIPEC16032	32	16	3,6	4	—
IPIPEC16040	40	16	3	4	—
IPIPEC16050	50	16	3,7	4	—
IPIPEC16063	63	16	4,7	4	—
IPIPEC16075	75	16	5,5	4	—
IPIPEC16090	90	16	6,6	4	—
IPIPEC16110	110	16	8,1	4	—
IPIPEC16140	140	16	10,3	4	—
IPIPEC16160	160	16	11,8	4	—
IPIPEC16225	225	16	16,6	4	—
IPIPEC16280	280	16	20,6	4	25,17
IPIPEC16315	315	16	23,2	4	31,89
IPIPEC16355	355	16	26,1	4	40,43
IPIPEC16400	400	16	29,4	4	51,32
IPIPEC10020	20	10	2	4	0,17
IPIPEC10025	25	10	2	4	0,22
IPIPEC10032	32	10	2	4	0,28
IPIPEC10040	40	10	2	4	0,36
IPIPEC10050	50	10	2,4	4	0,54
IPIPEC10063	63	10	3	4	0,85
IPIPEC10075	75	10	3,6	4	1,21
IPIPEC10090	90	10	4,3	4	1,74
IPIPEC10110	110	10	5,3	4	2,61

IPIPEC10140	140	10	6,7	4	4,21
IPIPEC10160	160	10	7,7	4	5,52
IPIPEC10225	225	10	10,8	4	10,9
IPIPEC10280	280	10	13,4	4	16,83
IPIPEC10315	315	10	15	4	21,2
IPIPEC10355	355	10	16,9	4	26,91
IPIPEC10400	400	10	19,1	4	34,27
IPIPEC10450	450	10	21,5	4	43,39
IPIPEC10500	500	10	23,9	4	53,59
IPIPEC10630	630	10	30	4	84,78