



3-х ходовой шаровой кран ТКД с эл.приводом 90-240V, муфтовые окончания, L-шар (уплотнение EPDM) PP-H d63 (DN50)

| Артикул      | d  | DN | PN | E   | H     | H1  | L    | Z      | B   | B1   | g    |
|--------------|----|----|----|-----|-------|-----|------|--------|-----|------|------|
| LKDIMEM016E1 | 16 | 10 | 10 | 54  | 118   | 80  | 14   | 89.5   | 205 | 29   | 1728 |
| LKDIMEM020E1 | 20 | 15 | 10 | 54  | 118   | 80  | 15   | 88     | 205 | 29   | 1728 |
| LKDIMEM025E1 | 25 | 20 | 10 | 65  | 145   | 100 | 16.5 | 112    | 216 | 34.5 | 1876 |
| LKDIMEM032E1 | 32 | 25 | 10 | 73  | 160   | 110 | 19   | 122    | 221 | 39   | 2014 |
| LKDIMEM040E1 | 40 | 32 | 10 | 86  | 188.5 | 131 | 23   | 142.5  | 238 | 46   | 2425 |
| LKDIMEM050E1 | 50 | 40 | 10 | 98  | 219   | 148 | 23.5 | 172    | 244 | 52   | 2652 |
| LKDIMEM063E1 | 63 | 50 | 10 | 122 | 266.5 | 179 | 27.7 | 211.15 | 261 | 62   | 3357 |