



FS ротаметр для NaOH 50%; корпус: полисульфон; поплавков с магнитом d50

| Артикул         | d  | Шкала для NaOH 50% [l/h] | B   | E   | C   |
|-----------------|----|--------------------------|-----|-----|-----|
| FSIV040P5X1100M | 40 | 50 - 1100                | 408 | 350 | 356 |
| FSIV040P5X2000M | 40 | 100 - 2000               | 408 | 350 | 356 |
| FSIV050P5X1000M | 50 | 50 - 1000                | 418 | 350 | 356 |
| FSIV075P5X0040M | 75 | 8200 - 40000             | 444 | 350 | 356 |
| FSIV032P5X0145M | 32 | 5 - 145                  | 400 | 350 | 356 |
| FSIV040P5X0550M | 40 | 25 - 550                 | 408 | 350 | 356 |
| FSIV063P5X6000M | 63 | 250 - 6000               | 432 | 350 | 356 |
| FSIV075P5X0125M | 75 | 500 - 12500              | 444 | 350 | 356 |
| FSIV025P5X0027M | 25 | 1 - 27                   | 394 | 350 | 356 |
| FSIV025P5X0070M | 25 | 2,5 - 70                 | 394 | 350 | 356 |
| FSIV025P5X0170M | 25 | 5 - 170                  | 394 | 350 | 356 |
| FSIV025P5X0350M | 25 | 15 - 350                 | 394 | 350 | 356 |
| FSIV032P5X0065M | 32 | 2,5 - 65                 | 400 | 350 | 356 |
| FSIV032P5X0330M | 32 | 10 - 330                 | 400 | 350 | 356 |
| FSIV032P5X0675M | 32 | 25 - 675                 | 400 | 350 | 356 |
| FSIV050P5X1900M | 50 | 50 - 1900                | 418 | 350 | 356 |
| FSIV050P5X2500M | 50 | 100 - 2500               | 418 | 350 | 356 |
| FSIV063P5X3100M | 63 | 100 - 3100               | 432 | 350 | 356 |
| FSIV075P5X9000M | 75 | 250 - 9000               | 444 | 350 | 356 |
| FSIV063P5X1800M | 63 | 50 - 1800                | 432 | 350 | 356 |