



Соединительная муфта GRIP Ø54.0-168.3, FKM, W5 d108

Артикул	Диаметр OD (мм)	Допуск на диаметр (мм)	PN (бар)	B (мм)	C (мм)	DV (мм)	X (мм)	Зазор без вкладки R (мм)	Зазор со вкладкой R (мм)	Крутящий момент Nm	sw(мм)	Резьба метрическая
G20942	125	123.7-126.3	623	115	53	152	174	5-10	5-30	40	6	12
G21112	133	131.7-134.3	423	115	53	160	182	5-10	5-30	40	6	12
G21165	139.7	138.3-141.1	120	115	53	166	189	5-10	5-30	40	6	12
G20494	70	68.9-70.1	722	65	24	87	104	5	5-15	15	6	8
G20656	88.9	88.0-89.8	326	100	40	112	134	5-10	5-25	20	6	10
G20584	79.5	78.7-80.3	332	100	40	103	125	5-10	5-25	20	6	10
G20957	127	125.7-128.3	823	115	53	154	176	5-10	5-30	40	6	12
G21052	130.2	128.9-131.5	125	115	53	157	179	5-10	5-30	40	6	12
G20506	73	72.3-73.7	721	65	24	90	107	5	5-15	15	6	8
G20678	95	94.0-96.0	24	100	40	117	139	5-10	5-25	25	6	10
G20606	84	83.2-84.8	329	100	40	107	130	5-10	5-25	20	6	10
G21208	141.3	139.9-142.7	220	115	53	168	190	5-10	5-30	40	6	12
G21331	165	163.4-166.6	616	115	53	192	214	5-10	5-30	50	6	12
G21369	168.3	166.6-170.0	106	115	53	195	217	5-10	5-30	50	6	12
G20360	54	53.5-54.5	524	65	24	71	87	5	5-15	15	6	8
G20865	108	106.9-109.1	922	100	40	132	154	5-10	5-25	25	6	10
G20906	114.3	113.2-115.4	524	100	40	138	160	5-10	5-25	25	6	10
G20932	118	116.9-119.1	922	100	40	142	166	5-10	5-25	35	6	10
G21262	154	152.5-155.5	518	115	53	181	203	5-10	5-30	50	6	12
G21309	159	157.4-160.6	106	115	53	186	208	5-10	5-30	50	6	12
G20406	57	56.4-57.6	523	65	24	74	90	5	5-15	15	6	8
G20456	60.3	59.7-60.9	923	65	24	77	93	5	5-15	15	6	8
G20427	63	62.4-63.6	523	65	24	80	96	5	5-15	15	6	8
G20476	66.6	64.9-67.3	322	65	24	84	100	5	5-15	15	6	8
G20558	76.1	75.3-76.9	935	100	40	100	122	5-10	5-25	20	6	10
G20692	98	97-99.0	24	100	40	121	143	5	5-25	35	6	10
G21227	144	142.6-145.4	520	115	53	171	183	5-10	5-30	60	6	12
G20706	100.6	99.6-101.6	83	100	40	124	146	5-10	5-10	25	6	10
G21006	129	127.7-130.3	823	115	53	156	178	5-10	5-30	40	6	12