



Муфта соединительная Straub-METAL-GRIP Ø30.0-219.1, NBR, W5 d48

Артикул	Диаметр OD (мм)	Допуск на диаметр (мм)	PN (бар)	B (мм)	C (мм)	DV (мм)	X (мм)	Зазор без вкладки R (мм)	Зазор со вкладкой R (мм)	Крутящий момент Nm	sw (мм)	Резьба метрическая
197	104	103.0-105.0	50	94	39	133	151	5-10	5-25	35	8	10
40651	108	106.9-109.5	35	94	39	133	151	5-10	5-25	35	8	10
40701	114.3	113.2-115.4	34	94	39	139	157	5-10	5-25	35	8	10
40601	129	127.7-130.3	33	108	43	160	182	5-15	5-25	60	10	12
40603	133	131.7-134.3	33	108	43	160	182	5-15	5-25	60	10	12
40611	139.7	138.3-141.2	32	109	43	168	191	5-15	5-25	60	10	12
40631												
40652												
41051	219.1	216.9 - 221.3	26	150	60	259	288	5-15	5-25	100	14	16
57	30	29.5-30.5	67	46/67	18	47	56	5	5	10	6	8
127	33.7	33.2-34.2	62	46/67	18	52	63	5	5	10	6	8
40101	38	37.5-38.5	58	61	19	58	73	5	5-10	15	6	8
40151	42.4	41.9-42.9	53	61	20	62	76	5	5-10	15	6	8
40201	44.5	44.0-45.0	48	61	20	80	56	5	5-10	15	6	8
40251	48.3	47.8-48.8	44	61	20	68	83	5	5-10	15	6	8
8670	54	53.5-54.5	39	77	38	74	89	5	5-15	15	6	8
11053	57	56.4-57.6	37	77	32	77	92	5-10	5-25	15	6	8
11055	60.3	59.7-60.9	37	77	32	82	95	5-10	5-25	15	6	8
212	63.5	62.9-64.1	37	77	32	84	98	5-10	5-25	15	6	8
192	73	72.2-73.8	56	94	39	95	117	5-20	5-25	35	8	10
40451	76.1	75.3-76.9	56	94	39	100	117	5-10	5-25	35	8	10
102278	84	83.2-84.8	45	94	39	112	123	5-10	5-25	35	8	10
40551	88.9	88.0-89.8	41	94	39	117	123	5-10	5-25	35	8	10