



Соединительная муфта GRIP Ø25.0-48.3, NBR, W5 d25

| Артикул | Диаметр OD (мм) | Допуск на диаметр (мм) | PN (бар) | B (мм) | C (мм) | DV (мм) | X (мм) | Зазор без вкладки R (мм) | Зазор со вкладкой R (мм) | Крутящий момент Nm | sw(мм) | Резьба метрическая |
|---------|-----------------|------------------------|----------|---------|--------|---------|--------|--------------------------|--------------------------|--------------------|--------|--------------------|
| G20101 | 33.7 | 33.2-34.2 | 339 | 46.5/75 | 18 | 51 | 65 | 5 | 5-10 | 10 | 6 | 8 |
| G20001 | 26.9 | 26.4-27.4 | 458 | 46.5/75 | 18 | 44 | 56 | 5 | 5-10 | 10 | 6 | 8 |
| G20026 | 28 | 27.5-28.5 | 550 | 46.5/75 | 18 | 45 | 57 | 5 | 5-10 | 10 | 6 | 8 |
| G20151 | 38 | 37.5-38.5 | 536 | 46.5/75 | 18 | 55 | 69 | 5 | 5-10 | 12 | 6 | 8 |
| G20176 | 40 | 39.5-40.5 | 535 | 46.5/75 | 18 | 57 | 71 | 5 | 5-10 | 12 | 6 | 8 |
| G20301 | 48.3 | 47.8-48.8 | 328 | 46.5/75 | 18 | 65 | 81 | 5 | 5-10 | 12 | 6 | 8 |
| G20251 | | | | | | | | | | | | |
| G19126 | 21.3 | 21.0-21.6 | 536 | 46.5/75 | 18 | 43 | 56 | 5 | 5-10 | 10 | 6 | 6 |
| G20040 | 25 | 24.5-25.5 | 564 | 46.5/75 | 18 | 41 | 53 | 5 | 5-10 | 10 | 6 | 8 |
| G20051 | 30 | 21.0-21.6 | 542 | 46.5/75 | 18 | 47 | 60 | 5 | 5-10 | 10 | 6 | 8 |
| G20125 | 35 | 34.5-35.5 | 537 | 46.5/75 | 18 | 52 | 66 | 5 | 5-10 | 12 | 6 | 8 |
| G20201 | 42.4 | 41.9-42.9 | 333 | 46.5/75 | 18 | 60 | 74 | 5 | 5-10 | 12 | 6 | 8 |