



Шаровой кран IVKD ХПВХ с эл.приводом 24V DC, фланцевые окончания d25 (DN20)

Артикул	Размер	DN	PN	D, мм	b, мм	D1, мм	d1, мм	n, мм	L, мм	L1, мм	L2, мм	H1, мм	H2, мм	C, мм	B1, мм	B2	E, мм	F, мм
IVKDOCEL020E	20	15	16	95	15	65	14	4	145	57	120	136,3	47,5	36	M5	6	-	31
IVKDOCEL025E	25	20	16	105	16	75	14	4	153	59	120	145,3	52,5	36	M5	6	-	35
IVKDOCEL032E	32	25	16	125	17	85	14	4	174	68	120	152,6	60	36	M5	6	-	42
IVKDOCEL040E	40	32	16	140	18	100	18	4	186	76	120	153,5	70	50	M6	8	-	56
IVKDOCEL050E	50	40	16	145	20	110	18	4	207	86,5	120	163,5	72,5	50	M6	8	-	58
IVKDOCEL063E	63	50	16	165	22	125	18	4	222	92	120	174,5	80	50	M6	8	-	70
IVKDOCEL075E	75	65	10	185	22	145	18	4	280	134	120	186,5	90	70	M8	10	30	84
IVKDOCEL090E	90	80	10	200	22	160	18	8	310	148	120	197	100	70	M8	10	32	90
IVKDOCEL110E	110	100	10	229	22	180	18	8	352	157	120	209,5	125	70/100	M8/10	10	40	100
IVKDOCEL020F	20	15	16	95	15	65	14	4	145	57	120	136,3	47,5	36	M5	6	-	31
IVKDOCEL025F	25	20	16	105	16	75	14	4	153	59	120	145,3	52,5	36	M5	6	-	35
IVKDOCEL032F	32	25	16	125	17	85	14	4	174	68	120	152,6	60	36	M5	6	-	42
IVKDOCEL040F	40	32	16	140	18	100	18	4	186	76	120	153,5	70	50	M6	8	-	56
IVKDOCEL050F	50	40	16	145	20	110	18	4	207	86,5	120	163,5	72,5	50	M6	8	-	58
IVKDOCEL063F	63	50	16	165	22	125	18	4	222	92	120	174,5	80	50	M6	8	-	70
IVKDOCEL075F	75	65	10	185	22	145	18	4	280	134	120	186,5	90	70	M8	10	30	84
IVKDOCEL090F	90	80	10	200	22	160	18	8	310	148	120	197	100	70	M8	10	32	90
IVKDOCEL110F	110	100	10	229	22	180	18	8	352	157	120	209,5	125	70/100	M8/10	10	40	100